

LAB REFRIGERATOR +1° / +10° C - SOLID DOOR

MODELS	VOLUME (Lt)	INNER DIMENSIONS (mm)			OUTER DIMENSIONS (mm)		
		W	D	H	W	D	H
LABREF100	96 L	485	455	435	620	665	800



CAPACITY	96 L
TEMPERATURE RANGE	+1° C / +10° C
AMBIENT TEMPERATURE	MAX. + 40° C
NO. OF COMPRESSOR	1
POWER	230V / 50 HZ
COMSUMPTION	LOW POWER CONSUMPTION
INSTALLATION	PLUG & PLAY
ALARMS	VISUAL / ACOUSTIC ALARM ▪ OPEN DOOR ALARM ▪ ADJUSTABLE HIGH / LOW TEMPERATURE ALARM ▪ CONTACT REMOTE ALARM
INTERFACE	RS485
ISOLATION	70 MM
WEIGHT	80 KG
SHELVES	1
MAX. SHELF LOAD	30 KG
CONTROLLOR	ELECTRONIC MICROPROCESSOR
CASTORS LOCKABLE	4 CASTORS - 2 LOCKABLE
DEFROST	AUTOMATIC
COOLING	AIR FORCED COOLING
DOOR KEY LOCK	YES
DOOR	MAGNETIC DOOR GASKET ▪ SELF-CLOSING DOOR ▪ SOLID DOOR
NO. OF DOORS	1
REFRIGERANT	R290
CONSTRUCTION	MONOBLOCK REFRIGERATION
CHAMBER MATERIAL	STAINLESS STEEL
EXTERIOR MATERIAL	POWDER COATED GALVANIZED STEEL

We reserve the right to change specifications without notice. Subject to confirmation, availability and errors.

B SCIENCE

Bavnevej 10 ▪ 6580 Vamdrup ▪ Denmark
 info@bscienceglobal.com ▪ www.bscienceglobal.com
 +45 287 287 62

